

REDEFINING EXPECTATIONS



BIG T600 SERVICE & WORKOVER UNIT

DRAWWORKS

ModelG42-154 (Band)
Single Line Pull41,000 lbs.

Hoisting Drum Information

Main Barrel Dimensions18.75 in. x 34 in.
Wire Line Size1 in.
Wire Line (optional)675 ft.
Drum Clutch24 in. 3-Plate
Gearing6 Forward / 1 Reverse
Drive ChainDouble 140
Brake System42 x 12 blocks
Brake CoolingAir/Water Spray

Sand Drum Information

Sand Drum Diameter12.75 in.
Standard Sand Line Size9/16 in.
Max. Sand Line Capacity16,000 ft.
Drum Clutch24 in. 2 Plate
Drive ChainSingle 140
Brake System42x8 blocks
Brake CoolingAir/Water Spray

MAST

Model112/265
Mast Height112 ft.

No. of Lines to the Block6 or 8
API Capacity265,000 lbs.
Drill Line Size1 in.
Racking Board Height58 ft. / 66 ft./74 ft.
Rod Basket Height78 ft.
Traveling Block150 ton, Non-Weighted

Mast Raising System

Raising Rams2-3 Stage, Double Acting
Telescoping Ram(1) Single Stage
Guy Lines(2) with Ratcheting Boomers
Wind Guys(1) Set with Tail Chains
Tubing Board Guys(1) Set with Tail Chains

POWER SYSTEM

EngineDetroit Series-60
Cylinders / Type6 / 4-Stroke
Horsepower475 Hp
Governed Speed2,100 RPM
Air CleanerSingle Dry Type
Emergency StopStandard

Transmission

ModelAllison 4500 OFS
Gearing6 Forward / 1 Reverse
Transfer CaseSpicer

AIR ELECTRICAL & HYDRAULIC

Compressor28 CFM
Electric System12 Volt
Alternator130 amp
Starter12 Volt
Batteries(3) BCI-31
Hydraulic System50 gpm / 2,000 psi

CAB

TypeSingle Person (Left drive)
Heater/Defroster40,000 BTU
Drivers SeatAir Ride
MirrorsBreak Away

RIG LEVELING SYSTEM

Leveling Jacks(4) 12 in. Hyd. w/ Manual Lock
(2) Screw Type

CARRIER

Type5 axle
Length w/ Mast66 ft. 6 in.
Overhang, Front19 ft. 2 in.
Height (OTR)14 ft. 3 in.
Estimated Rig Weight96,620 lbs.

AXLES - SUSPENSION

FrontTandem / Steerable
Axle Capacity20,000 lbs. per axle
Suspension TypeSpring
RearWalking Beam w/ Air Tag
Pusher Axle Capacity20,000 lbs.
Tag Axle Capacity20,000 lbs.

Brakes

ABS SystemStandard Drum
Park BrakeAir

Tires & Wheels

Front Tires425/65 R22.5 in.
Wheels (Steel)13 in. / 22.5 in.
Rear Tires11R 22.5 in.
Rear Wheels (Steel)8 in. / 22.5 in.

Frame

Main Rails21 in.
Frame DeckDiamond Plate
Tow PointsFront & Rear

Paint

Standard Paint2 Non-Metallic Colors
----------------	----------------------------

LEGENDARY TAYLOR QUALITY.
EXCEPTIONAL SERVICE SUPPORT.